

Saturn 5000

Fully Integrated, Highly Secure, Contactless Payment Reader

OTI's **Saturn 5000** is the ultimate contactless card reader powering contactless payment and loyalty programs, providing unsurpassed cost-to-performance results.

Supporting such major financial contactless programs, as **MasterCard's PayPass™**, the **Saturn 5000** reads data from a variety of sources, including credit cards and key fobs that comply with **ISO 14443 type A and B** (with Mifare support).

The **Saturn 5000** uses OTI's patented matched antenna technology to provide:

- More effective power consumption
- Reliable and stable communication
- Additional levels of security and encryption throughout the communication link.

The highly sophisticated, stylishly designed **Saturn 5000** reader supports programmable LEDs with buzzer to give user feedback for convenience. The **Saturn 5000** is designed to occupy minimum shelf space. It can be placed on the counter with various stands and fit different environments, drive thru, box office window and more.

Saturn 5000's plug-and-play design makes it easy to **connect to your existing infrastructure and POS terminal**, quickly upgrading it to contactless operations without disrupting your on going business operations.





Interface Options to POS

- RS232 Interface
- RS485 Interface
- USB Interface
- MSR Coil Interface
- MSR Head Interface
- MSR PS2 Interface
- MSR RS232 Interface

Standards

- Compliant to ISO 14443 Type A & B (with Mifare support)
- FCC part 15 and EN 301 489-3
- *PayPass* compliant

Secure and Flexible Platform

- Integrated, sophisticated Smart Card Operating System on board
- Flexible, software-configurable design
- On-board EMV2000 compliant SAM support
- High security encryption system (DES/RSA)
- In-system programming of reader firmware to 128KB flash memory via standard RS232 / RS485 / USB communication

General Features

- Dimensions: 6.4" (163mm) H x 4.2" (107mm) W x 0.75" (19mm) D
- Proximity range - up to 4 inches (10 cm)
- 4 In board Indicator LEDs and 4 programmable LEDs.
- Power input from 6.5 to 15VDC / 1.35W



side view

 www.otiglobal.com

On Track Innovations, Ltd.
ZHR Industrial Zone
P.O. Box 32
Rosh Pina, 12000
Israel
Tel: +972-4-6868000
Fax: +972-4-6938887
info@otiglobal.com

OTI America
1601 S. De Anza Blvd.
Suite 201
Cupertino, CA 95014
USA
Tel: 408-252-0333
Fax: 408-252-8414
info@otiamerica.com

OTI Africa
10th Floor, Park on Long
64 Long Street
Cape Town, 8001
South Africa
Tel: +27-21-422-1940
Fax: +27-21-422-1969
chambly@iafrica.com